

Deck mounted swivel basin spout



Copyright © 2024 www.chilli-b.co.za

SKU: CB-DSP-4410

Features:

- Swivel spout.
- 30mm diameter base made from stainless steel.
- Flow reducers to save water optional.
- Optional aerators to reduce splashing making hand washing more hygienic than other spouts.
- 201(h) x 115(w) mm gives enough reach in most small to compact basins. Spout outlet is 123mm high.

DESCRIPTIONS

Deck mounted spouts are used with hands free knee or foot operated valves/taps. The spouts require a 22mm diameter hole cut into the basin. A standard 15mm male BSP thread is connected with the water supply (either foot or knee valve). The CB-DSP-4410 can be used with flow limiter, 1.3 L/min or 6 L/min with fine aerator to reduce splashing which makes it more hygienic. Reducing flow rate of a basin spout below 6L/min conforms to "SANS10252 part1(National Regulation): 6.1.4.4 Terminal fitting flow controller". This is significant as unrestricted spouts, such as the W-SSP/15, can use up to 20 L/min. The only way to reduce water flow is in the foot or knee valve that supplies the water.



Optional flow restrictors with aerators for CB-DSP-4410 deck mounted swivel spout



SW-NE70410998
Flow rate 1.3 L/min.



SW-NE70411198
Flow rate 6 L/min.



SW-NE70411398
Housing only for
SW- NE70410998 &
SW- NE70411198



SW-NE70410298
Aerator with flow rate
7.5-9.0 L/min.

SANS10252 part1 (National Regulation) 6.1.4.4